

SPECIFICATION

Quality		: BALTIC
Product definition		: tufted loop pile
Gauge		: 1/10"
Pile fibre		: 100% polyamide SD
Pile weight		: 550 gr/m ²
Pile height	ISO 1766	: 3.0 mm
Tile backing		: Bitumen
Total thickness	ISO 1765	: 5.0 mm
Total weight		: 4000 gr/m ²
Tile size		: 50 x 50 cm

PERFORMANCE

Use classification		: Class 33
Castor chair test	EN 985	: A, continuous use
Abrasion	EN 1963	: pass
Vettermann test	ISO TR 10361/EN 1471	: pass
Dimensional stability	EN 986	: pass
Thermal isolation	ISO 8302	: 0.06 m ² K/W
Sound absorption	ISO 140-8	: 20 dB
Luxury class	LC2	: LC2
DOP-nr		: 1016-2612
Prodis-nr		: In application

ELECTROSTATIC PROPERTIES

Static loading		: Anti-static
Walking test	EN 1815	: ≤0. 3kV
Horizontal resistance	ISO 1096 5	: 5 x 10.10 Ohm
Vertical resistance	ISO 1096 5	: 5 x 10.10 Ohm

FLAMMABILITY

Reaction to fire	EN ISO 9239-1	: B _{fl} – s1
------------------	---------------	------------------------

COLOUR FASTNESS

Light	ISO 105 B02	: 7.0 – 8.0
Rubbing	ISO 105 X12	: 4.5
Water	ISO 105 X12	: 5.0

GENERAL

Maintenance: Regular vacuum cleaning is essential. Spills and surface stains can be removed by sponging with a damp cloth, or for more resistant stains, with a mild detergent solution.

