

SPECIFICATION

Quality		: LARIX
Product definition		: tufted loop pile
Gauge		: 5/32"
Pile fibre		: 100% polyamide SD
Pile weight		: 600 gr/m ²
Pile height	ISO 1766	: 3.5 mm
Tile backing		: Polyflex
Total thickness	ISO 1765	: 7.2 mm
Total weight		: 4200 gr/m ²
Tile size		: 50 x 50 cm

PERFORMANCE

Use classification		: Class 33
Castor chair test	EN 985	: A, continuous use
Abrasion	EN 1963	: pass
Vettermann test	ISO TR 10361/EN 1471	: pass
Dimensional stability	EN 986	: pass
Thermal isolation	ISO 8302	: 0.09 m ² K/W
Sound absorption	ISO 140-8	: 25 dB
Luxury class	LC2	: LC2
DOP-nr		: 1016-2612
Prodis-nr		: D5B5C3F9

ELECTROSTATIC PROPERTIES

Static loading		: Anti-static
Walking test	EN 1815	: ≤0.1kV
Horizontal resistance	ISO 1096 5	: 8 x 10.9 Ohm
Vertical resistance	ISO 1096 5	: 4 x 10.9 Ohm

FLAMMABILITY

Reaction to fire	EN ISO 9239-1	: B _{fl} -s1
------------------	---------------	-----------------------

COLOUR FASTNESS

Light	ISO 105 B02	: ≥5.0
Rubbing	ISO 105 X12	: 4.5
Water	ISO 105 X12	: 5.0

GENERAL

Maintenance: Regular vacuum cleaning is essential. Spills and surface stains can be removed by sponging with a damp cloth, or for more resistant stains, with a mild detergent solution.

