

Feature

Style Number	5T385	
Collection	Auxiliary	
Product Type	Carpet Tile	
Construction	Standard	Data + Performance
Type of Manufacture	ISO 2424	tufted 1/12" 47.2 per 10cm
Aspect	ISO 2424	Level Loop
Dye Method	EN 994	100% Solution Dyed
Dimensions	EN 994	50 cm x 50 cm 20 tiles (5 m²) per box
Primary Backing	ISO 2424	Pet Non-Woven
Secondary Backing	ISO 2424	Taskworx@tile Polymer Modified Bitumen
Pile Fibre Composition	ISO 2424	Aquafil Polyamide 6
Total Thickness	ISO 1765	5.1 mm
Effective Pile Thickness	ISO 1766	1.0 mm
Total Mass	ISO 8543	4248 g/m²
Nominal Total Pile Mass	ISO 2424	450 g/m²
Effective Pile Mass	ISO 8543	126 g/m²
Pile Density	ISO 8543	0.121 g/cm³



Performance


Number of Tufts	ISO 1763	184,000/m² 39 per 10 cm
Electrostatic Propensity	ISO 6356	≤ 2.0 kv (Stroll Test)
Use Classification	EN 1307	33 commercial heavy
Luxury Class	EN 1307	LC1
Dimensional Stability	EN 986	≤ 0.2%
Impact Sound Insulation	ISO 10140	21dB
Sound Absorption Classification	ISO 354/11654	0.10 α_w
Thermal Resistance m ² K/W	ISO 8302	0.046 m² K/W TOG 0.46
Dry Slip Resistance	ISO 13893	pass
Colour Fastness to Light	ISO 105-B02	>6
Flammability	EN 13501-1	Bfl-S1 (adhered testing)
Castor Chair	EN 948	≥2.4 Continuous Use

10 Year Commercial Limited Warranty subject to installation in full accordance with manufacturer's instructions and a regular effective cleaning and maintenance programme.


Recommended Installation Method



Quarter Turn



Random



Brick

Coordinating Products

Carpet Tile: **Complement, Detail**



21dB 0.10 α_w

Corporate Headquarters +1 800 257 7429 | +1 706 532 7984 | Atlanta +1 404 853 7429 | Bengaluru +91 80 6773 0202 | Beijing +86 10 6568 588 | Chicago +1 312 467 1331 | Dubai +971 4 584 6956 | Hong Kong +852 2623 0371 | Latin America (Miami) +1 305 827 5912 | London +44 207 961 4120 | Los Angeles +1 800 233 1614 | Melbourne +61 3 9939 8543 | Mexico City +55 5010 7600 | Mumbai +91 22 6284 5050 | Nantong +86 400 800 7429 | New York +1 212 953 7429 | Paris +33 (0) 1 81 22 44 39 | San Francisco +1 415 955 1920 | Santiago +562 2431 5000 x550 | São Paulo +55 11 3071 1702 | Shanghai +86 21 3338 4000 | Singapore +65 6733 1811 | Sydney +1 800 556 302

CE
07
EN14041
DOP 0338/CPR/0517/0917/BT
Manufactured by: SHAW EUROPE LTD. BLACKADDIE
ROAD INDUSTRIAL ESTATE, SANQUHAR, DG4 6DB, UK

E1
HCHO

Bfl-s1

DS

Taskworx@Tile | Polymer Modified Bitumen Carpet Tile for
use as an indoor floor covering as specified by the
manufacturer
Notified Body Number 0338

Product Transparency

Shaw Contract is dedicated to providing clients with a building chemistry that's safe and dependable. Working together, we will help you meet your goals as they pertain to material health. Taskworx products are Cradle to Cradle Certified™ Bronze and assessed for impacts on human health and the environment. This product can be recycled. When it's time to replace, we can collect through our re-[TURN] scheme in EMEA.

Attributes + Certifications

Cradle to Cradle Certified™

Environmental Product Declaration (EPD)

Environmental Guarantee*

Country of Origin**

Bronze Level (Version 3.1)

3rd Party Certified in Accordance with ISO 14044, ISO 14025 & EN15804

Take Back Policy Offered For All Taskworx Products

United Kingdom

LEED Contribution Credit

MR Credit: Building Product Disclosure and Optimization
Environmental Product Declarations - Option 1: Environmental Product Declaration (EPD)

3rd Party Certified in Accordance with ISO 14044, ISO 14025 & EN15804

MR Credit: Building Product Disclosure and Optimization
Material Ingredients - Option 1: Material Ingredient Reporting

HPD (Version 2.1) or C2C Bronze Level (Version 3.1)

MR Credit: Building Product Disclosure and Optimization
Material Ingredients - Option 2: Material Ingredient Optimization

C2C Bronze Level (Version 3.1)

Additional Information

**Meets or exceeds all local and national regulations in country of manufacture.

[Installation Guidelines](#)

[Maintenance Guidelines](#)


Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.

This product is an exclusive design and may not be duplicated in any manner. Use of this design in the creation of another product design is also strictly prohibited.


Visit shawcontract.com/testing for more information.




Light Reflectance Value




LRV 11.7 (range 8.6 - 18.0)
Smoke Spring 83326




LRV 10.2 (range 8.6 - 12.3)
Smoke Azure 83486



LRV 7.3 (range 4.7 - 9.7)
Smoke Black 83505




LRV 10.8 (range 6.4 - 15.8)
Pebble Ash 83535




LRV 12.1 (range 16.6 - 82.3)
Smoke Ice 83536



LRV 6.5 (range 4.2 - 8.7)
Pebble Flint 83549



LRV 8.4 (range 6.6 - 10.1)
Pebble Coral 83866



LRV 8.6 (range 7.3 - 10.8)
Pebble Blossom 83870